

L.P.G. Gas

L.P.G. Kaynak



TUBE : BLACK, LPG AND RESISTANT SPECIAL SYNTHETIC RUBBER.
 REINFORCEMENT : HIGH TENSILE SYNTHETIC TEXTILE,
 COVER : ABRASION, FLAME, OZONE AND WEATHER RESISTANT, ORANGE COLOUR SMOOTH SYNTHETIC RUBBER.
 APPLICATION : FOR LPG WELDING.



SEELE : SCHWARZER, LPG-GASBESTÄNDIGER SPEZIAL SYNTHETIK-KAUTSCHUK.
 EINLAGEN : HOCH REISSFESTE SYNTHETISCHE TEXTILEINLAGE.
 DECKE : FLAMMWITRIG, ABRIEBFEST-, OZON- UND WITTERUNGSBESTÄNDIGER, GLATTER SYNTHETIK-KAUTSCHUK; FARBE: ORANGE.
 ANWENDUNG : GEEIGNET ALS SCHWEISSSCHLAUCH SOWIE PROPANGAS.



SOTTOSTRATO : NERO, LISCIO IN GOMMA SINTETICA RESISTENTE AL GPL E GAS DOMESTICO.
 RINFORZO : INSERZIONI TESSILI AD ALTA TENACITÀ.
 COPERTURA : GOMMA SPECIALE SINTETICA RESISTENTE ALL'ABRASIONE, FIAMMA, OZONO E AGENTI ATMOSFERICI.
 IMPIEGO : PER MANDATA DI GPL.



ALT KAT : GAZ HALİNDEKİ LPG'E DAYANIKLI ÖZEL SİYAH DÜZ SENTETİK KAUKÇUK.
 TAKVIYE : YÜKSEK MUKAVEMETLİ SENTETİK TEKSTİL.
 ÜST KAT : ALEVE, AŞINMAYA VE HER TÜRLÜ HAVA ŞARTLARINA DAYANIKLI TURUNCU ÖZEL SENTETİK KAUKÇUK.
 KULLANIM YERİ : BÜTAN VE PROPANLA KAYNAK YAPMA İŞLERİNDE, LPG VE GAZ NAKLETME İŞLERİNDE.



ID/iç		OD/DÇ		WP/ÇB		BP/PB		BR/KY/r		W/A		L/B	
inch	mm	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt			mt	
1/4	6	14	20	290	60	870	60	192			10-100		
5/16	8	16	20	290	60	870	80	230			10-100		
3/8	10	18	20	290	60	870	100	268			10-100		
1/2	12,7	22,5	20	290	60	870	127	415			10-100		



-25°C / +110°C
 -13°F / +230°F

NORMS BS 3212 - TYPE2
 NORMEN BS 5120 - CLB TYPE N
 NORME TS 2411 EN 559
 NORMLAR ISO 1307

MARKING
 BESCHRIFTUNG
 MARCATURA
 MARKALAMA

EMBOSSED
 INK

COLOUR
 FARBEN
 COLORI
 RENKLER

