

Welding

Oksijen ve Asetilen Kaynak



TUBE : BLACK SMOOTH SYNTHETIC RUBBER RESISTANT TO OXYGEN AND ACETYLEN GAS.
 REINFORCEMENT : HIGH TENSILE SYNTHETIC TEXTILE,
 COVER : ABRASION, WEATHER AND FLAME RESISTANT, BLUE FOR OXYGEN, RED FOR ACETYLEN SPECIAL SYNTHETIC RUBBER.
 APPLICATION : FOR INDUSTRIAL WELDING.



SEELE : SCHWARZER, GLATTER, SYNTHETIK KAUSCHUK, BESTÄNDIG GEGEN AZETYLEN UND SAUERSTOFF.
 EINLAGEN : HOCH REISSFESTE SYNTHETISCHE TEXTILEINLAGE.
 DECKE : ABRIEBFEST-, OZON- UND WITTERUNGSBESTÄNDIGER SPEZIAL KAUSCHUK, FARBE FÜR SAUERSTOFF BLAU; AZETILEN: ROT.
 ANWENDUNG : FÜR INDUSTRIELLES SCHWEISSEN.



SOTTOSTRATO : NERO, LISCIO IN GOMMA SINTETICA RESISTENTE ALL'AZIONE DEI GAS DI SALDATURA.
 RINFORZO : INSERZIONI TESSILI AD ALTA TENACITÀ.
 COPERTURA : GOMMA SPECIALE SINTETICA RESISTENTE ALL'ABRASIONE, OZONO, FIAMMA E AGENTI ATMOSFERICI. BLU PER OSSIGENO E ROSSO PER ACETILENE.
 IMPIEGO : PER SALDATURA INDUSTRIALE.



ALT KAT : OKSİJEN VE ASETİLENE DAYANIKLI ÖZEL SİYAH DÜZ SENTETİK KAUKUK.
 TAKVİYE : YÜKSEK MUKAVEMETLİ SENTETİK TEKSTİL.
 ÜST KAT : ALEVE, AŞINMAYA, VE HER TÜRLÜ HAVA ŞARTLARINA DAYANIKLI ÖZEL SENTETİK KAUKUK. OKSİJEN İÇİN MAVİ, ASETİLEN İÇİN KIRMIZI RENKLERDE.
 KULLANIM YERİ : ENDÜSTRİYEL OKSİJEN VE ASETİLEN KAYNAĞI İŞLERİNDE.



ID/iç		OD/DÇ	WP/ÇB		BP/PB		BR/KY/r	W/A	L/B
inch	mm	mm	BAR	PSI	BAR	PSI	mm	gr/mt	mt
1/4	6	13	20	290	60	870	60	160	10-100
1/4	6	14	20	290	60	870	60	191	10-100
5/16	8	15	20	290	60	870	80	193	10-100
5/16	8	16	20	290	60	870	80	230	10-100
	9	16	20	290	60	870	90	212	10-100
3/8	10	17	20	290	60	870	100	227	10-100
3/8	10	18	20	290	60	870	100	270	10-100
1/2	12.7	22	20	290	60	870	127	385	10-100



-25°C / +110°C
 -13°F / +230°F

NORMS NORMEN NORME NORMLAR	UNI EN 559 / ISO 3821 / DIN 8541 TS 2411 EN 559 / NFT 47-220 ISO 1307	MARKING BESCHRIFTUNG MARCATURA MARKALAMA	EMBOSSED	COLOUR FARBEN COLORI RENKLER	 
-------------------------------------	---	---	----------	---------------------------------------	---

