

Oil Nitrile Tube Saf Nitril



TUBE APPLICATION : OIL AND FUEL RESISTANT NITRILE RUBBER.
: OIL RETURN SERVICES.



SEELE ANWENDUNG : ÖL-UND KRAFTSTOFFBESTÄNDIGER NITRIL-GUMMI.
: ÖL-UND KRAFTSTOFFRÜCKLAUF.



SOTTOSTRATO IMPIEGO : GOMMA NITRILE NERA, RESISTENTE AGLI OLI ED AL GASOLIO.
: MANDATA DEL GASOLIO E DELLA BENZINA.



ALT KAT KULLANIM YERİ : MAZOTA, BENZİNE VE YAĞLARA DAYANIKLI NITRİL KAUÇUK.
: GENEL AMAÇLI YAKIT İLETİM İŞLERİNDE.

ID/iç mm	OD/Dç mm	WP/ÇB		BP/PB		BR/KY/r mm	W/A g/m	L/B m
		bar	psi	bar	psi			
3,2	6	-	-	-	-	-	29	+10
3,5	6,5	-	-	-	-	-	34	+10
4	7	-	-	-	-	-	37	+10
4,5	8	-	-	-	-	-	49	+10
5	9	-	-	-	-	-	63	+10
5,5	9,5	-	-	-	-	-	68	+10
6	10	-	-	-	-	-	72	+10
7	11	-	-	-	-	-	81	+10
7,5	11	-	-	-	-	-	73	+10
8	12	-	-	-	-	-	90	+10
10	14	-	-	-	-	-	108	+10
12	18	-	-	-	-	-	203	+10
16	22	-	-	-	-	-	257	+10
19	26	-	-	-	-	-	360	+10

Other diameters available upon request.
Weitere Abmessungen auf Anfrange möglich
Altri diametri realizzabili su richiesta.
Diğer ölçüler istek üzerine üretilebilir.



-35°C / +70°C
-31°F / +158°F

NORMS NORMEN NORME NORMLAR	ISO 1307	MARKING BESCHRIFTUNG MARCATURA MARKALAMA	INK-JET	COLOUR FARBEN COLORI RENKLER	
-------------------------------------	----------	---	---------	---------------------------------------	--

